




## SPEZIFIKATIONEN

GÄNGE	12-SPEED	SATTELSTÜTZE	BIXS SP-719, 15" & 17": 350MM, OTHERS: 400MM, 31.6MM
RAHMEN	SPORT GEOMETRY ALLOY 6061 HYDROF. T.B., DROPOUT 148X12MM BOOST, HARDTAIL 29"	SATTEL	ERGON SR10 SPORT
RAHMENGRÖSSE	15",17",19",21"	FELGEN	ALEXRIMS EXR-27, 32 HOLES, INNER WIDTH 27MM, 29"
GABEL	ROCK SHOX REBA RL 29", SOLO AIR SPRING, TAPERED, 15X110MM AXLE, 100MM TRAVEL, REBOUND, LOCKOUT	VORDERE NABE	SHIMANO XT HB-M8110-B, 32 HOLES, 15X110MM THRU AXLE
VORBAU	BIXS AS-M03, 0° ANGLE, 31.8MM CLAMP	HINTERE NABE	SHIMANO XT FH-M8110-B, 32 HOLES, 12X148MM BOOST THRU AXLE
STEUERSATZ	FSA NO.57, 1-1/8" UPPER AND 1.5" LOWER BEARING WITH 5.3MM TOP COVER	KASSETTE	SHIMANO CS-M7100, 10-51 THEETH, 12-SPEED
LENKER	BIXS HB-RB12W RIZER BAR, 760MM, 9° ANGLE, 25MM RISE, 31.8MM	KETTE	SHIMANO CN-M8100 12-SPEED
SCHALTWERK	SHIMANO XT RD-M8100 SGS SHADOW PLUS DESIGN, 12-SPEED	REIFEN	SCHWALBE ROCKET RON PERFORMANCE, ADDIX, 29X2.25"
SCHALTHEBEL	SHIMANO XT SL-M8100, DIRECT ATTACH TO BRAKE LEVER, ISPEC EV	GEWICHT	11.4 KG
BREMSHEBEL	SHIMANO XT BL-M8100, ISPEC EV	ARTIKELNUMMER	101-506-1073
BREMSEN	SHIMANO XT BR-M8100, HYDRAULIC DISC BRAKE, RESIN PADS, F:180MM, R:180MM ROTORS		
KURBELGARNITUR	SHIMANO XT FC-M8100-1, HOLLOWTECH II, 32 TEETH		
INNENLAGER	SHIMANO BB-MT800		
PEDALE	WELLGO WPD-823, WITH CLEAT		

## GEOMETRIE

SIZE	A	B	C	D	E	F	G	H	I	J	K
15"	380	570	105	450	73°	69°	1089	35	621	380	300
17"	430	590	110	450	73°	69°	1110	45	626	399	300
19"	480	610	120	450	73°	69°	1130	55	635	415	300
21"	530	630	130	450	73°	69°	1156	65	645	432	300



A	Rahmengrösse
B	Oberrohr horizontal mm
C	Steuerrohr mm
D	Kettenstreben mm
E	Sitzwinkel Grad
F	Steuerrohrwinkel Grad
G	Radstand mm
H	Vorbau mm
I	Stack mm
J	Reach mm
K	Tretlagerhöhe mm

## GRÖSSENRECHNER

KÖRPERGRÖSSE / TAILLE	149–163 cm	159–178 cm	174–188 cm	185–200 cm
FAHRRADGRÖSSE	15"	17"	19"	21"

NOTIZEN / FIRMENSTEMPEL